



Dual Phase Extraction System
Air stripper/Oilwater Separator/Bag filter/
Carbon polisher/Air Compressor/SVE
Unit#148

Environmental Treatment Specialists



- General Specifications: 30 GPM
500 CFM @ 22" Hg
- Trailer: 8ft wide x 32 ft long x 9 ft height
21,550 pound triple axles
- Main Equipment: Travaini Liquid ring pump 40 Hp XP motor
120 gallon knock out tank w/2HP Moyno pump
3 – electric submersible pumps
30 GPM stainless steel Oil/Water Separator
55 gallon product holding tank
3 Hp 30 GPM 20 PSI to feed Air Stripper
30 GPM stainless steel Air Stripper
5 Hp Air Stripper Blower
30 GPM 3 HP @ 40 PSI water pump
2 LCO8 Bag Filters (after Air Stripper)
2-800 pound stainless steel granular activated carbon filters
Flow Meter
All required plumbing
Pressure gauges and sample ports
- Trailer Specifications: XP Lights, XP heater inside insulated trailer
- Control Panel: EOS PLC with data logging and remote Operation
All pumps HAO switch
High level shut off on product drum, Oil/Water Separator and Air Stripper sump. Floor sump
Interlock connections
- Inlet Hose Connection: 3 - Male camlock 1" inlet connections
6 - Male camlock 2" inlet connections
- Outlet Hose Connection: Male camlock 2" discharge outlet fitting
4" diameter 18 ft height stack for Air Stripper off gasses (can have option to treat)
- Power Requirements: 240 Volt, 1 phase, 200 Amp services
(Main fused disconnect located outside trailer)

ProAct Services Corporation

Corp Office: 231-843-2711
Gulf Coast: 210-862-6467
or 713-202-6351
Midwest Office: 231-342-1115
East Coast Office: 203-262-1200

www.proact-usa.com

Texas • Colorado • Michigan • New Jersey • Connecticut