



## Water Treatment System Air Stripper/Oilwater Separator/Bag Filter/ Carbon Polisher Unit# 151

### Environmental Treatment Specialists



#### ProAct Services Corporation

Corp Office: 231-843-2711  
Gulf Coast: 210-862-6467  
or 713-202-6351  
Midwest Office: 231-342-1115  
East Coast Office: 203-262-1200

[www.proact-usa.com](http://www.proact-usa.com)

General Specifications: 50 GPM

Trailer: 8ft wide x 32 ft long x 9 ft height  
21,550 pound triple axles

Main Equipment: 3 Hp 50 GPM 40 PSI pump to feed to O/W Separator  
50 GPM Oil/Water Separator  
55 gallon product holding tank  
2 Hp 50 GPM 20 PSI to feed Air Stripper  
80 GPM Air Stripper  
7.5 Hp Air Stripper Blower  
50 GPM 2 HP @ 40 PSI water pump  
2 LCO8 Bag Filters (after Air Stripper)  
4-800 pound steel granular activated carbon filters  
Flow Meter  
All required plumbing  
Pressure gauges and sample ports

Trailer Specifications: XP Lights, XP heater inside insulated trailer

Control Panel: All pumps HAO switch  
High level shut off on product drum, Oil/Water Separator and Air Stripper sump.  
Interlock connections

Inlet Hose Connection: 5 Male camlock 2" inlet connections

Outlet Hose Connection: 1 Male camlock 2" discharge outlet fitting  
1 Male camlock 2" backwash outlet fitting  
4" diameter 18 ft height stack for Air Stripper off gasses ( can have option to treat)

Power Requirements: 240 Volt, 3 phase, 200 Amp services  
(Main fused disconnect located outside trailer)

Texas • Colorado • Michigan • New Jersey • Connecticut