



Ozone Injection System Unit# 195

Environmental Treatment Specialists



General Specifications: Ozone Injection System
6 pounds/day 111g/hr of Ozone

Trailer: 8ft wide x 16 ft long x 7 ft height
3,500 pound double axle trailer

Main Equipment: 6 pound/day. HC-6.0 Ozonation System
2-5 HP Rotary Screw Air Compressors
80 cfh Air Sep Oxygen Generator
120 gallon Holding Tank
Pressure gauges
40 gallon Air Pressure Tank
Ozone Leak Detector
12 Well Manifold, 4 banks of 3 wells
(can be customized for other well configurations)
Flow Meters, control flow valves and pressure gauges each well



Trailer Specifications: Insulated Trailer
Lights, heater, fan in equipment room
Aluminum diamond plated floor
Outside lights

Control Panel: HAO switch – all components
4 timers, one for each bank of 3 wells
Emergency stop button
GFI

Inlet hose connections: none

Outlet hose connections: 12 3/8" Air feed

Power Requirements: 220 Volt, 1 phase, 100 Amp services
(Main fused disconnect located outside trailer)



ProAct Services Corporation

Corp Office: 231-843-2711

Gulf Coast: 210-862-6467

or 713-202-6351

Midwest Office: 231-342-1115

East Coast Office: 203-262-1200

www.proact-usa.com

Texas • Colorado • Michigan • New Jersey • Connecticut