



## Thermal/Catalytical Oxidizer Electric Unit# 26, 37 and 44

### Environmental Treatment Specialists



General Specifications: 300 SCFM @20" H2O

Trailer: 8 ft wide x 16 ft long x 10 ft height  
3,500 pound skid

Main Equipment: 10HP Regenerative Blower  
Flame Arrestor  
Heat Exchanger  
Electric fired  
Stainless Steel Reactor  
Catalyst  
Inlet and Outlet Temperature Controls  
Completely enclosed system

Trailer Specifications: System can be mounted on back of flat bed trailer

Control Panel: PLC (Program Logic Controller)  
On/Off switch all components  
Emergency stop button  
Fault lights and reset  
Interlock connections

Inlet Hose Connection: 4" inlet fittings  
Auto dilution valve

Outlet Hose Connection: 10" air stack from top of enclosure (15 ft high)

Power Requirements: 230 volt, 3 phase, 100 Amp service

#### ProAct Services Corporation

Corp Office: 231-843-2711

Gulf Coast: 210-862-6467

or 713-202-6351

Midwest Office: 231-342-1115

East Coast Office: 203-262-1200

[www.proact-usa.com](http://www.proact-usa.com)

Texas • Colorado • Michigan • New Jersey • Connecticut