



Dual Phase Extraction System Liquid Ring Pump/SVE Unit#287

Environmental Treatment Specialists



General Specifications: 1,000 ACFM max @ 26" Hg max
30 GPM removal

Trailer: 8ft wide x 24 ft long x 13 ft height
14,000 pound double axles

Main Equipment: Travaini Liquid ring pump 75 Hp XP motor
220 gallon knock out tank
Two -2HP Moyno pumps
Air and Water Flow Meters
All required plumbing
Pressure gauges and sample ports, temperature
gauges, valves, pressure and vacuum transmitters

Trailer Specifications: XP Lights, XP heater inside insulated trailer
2 room trailer, control room and process room

Control Panel: EOS PLC with data logging and remote Operation
All components contain HAO switches
Alarm indicator lights, reset switch
High level shut off on floor sump
Interlock connections

Inlet Hose Connection: 5 - Male camlock 3" inlet connections including pitot
tubes, flow control valve, site tube, vacuum gauge for
each leg stainless steel manifold

Outlet Hose Connection: 1-Male camlock 6" discharge outlet fitting
or 15 ft height stack
1- Male camlock 2" liquid

Power Requirements: 480 Volt, 3 phase, 200 Amp services
(Main fused disconnect located outside trailer)

ProAct Services Corporation

Corp Office: 231-843-2711
Gulf Coast: 210-862-6467
or 713-202-6351
Midwest Office: 231-342-1115
East Coast Office: 203-262-1200

www.proact-usa.com

Texas • Colorado • Michigan • New Jersey • Connecticut