



Water Treatment System
Air Stripper/Oil/water Separator
Bag filter/Carbon polisher
Unit# 48

Environmental Treatment Specialists



ProAct Services Corporation

Corp Office: 231-843-2711
Gulf Coast: 210-862-6467
or 713-202-6351
Midwest Office: 231-342-1115
East Coast Office: 203-262-1200

www.proact-usa.com

General Specifications: 50 GPM

Trailer: 8ft wide x 24 ft long x 9 ft height
7,550 pound double axle trailer

Main Equipment: 3 HP 50 GPM 40 PSI pump to feed O/W Separator
50 GPM Oil/Water Separator
55 gallon product holding tank
1.5 HP 50 GPM 20 PSI pump to feed Air Stripper
80 GPM Air Stripper
7.5 HP Air Stripper Blower
50 GPM 3HP @40 PSI water pump
2 - LCO8 Bag Filters (Before the Air Stripper)
2 - LCO8 Bag Filters (After the Air Stripper)
2-800 pound granular activated media filters
Flow Meter
All required plumbing
Pressure gauges and sample ports

Trailer Specifications: XP Lights, XP heater inside insulated trailer

Control Panel: All pumps HAO switch
High level shut off on product drum, Oil/Water Separator
and Air Stripper sump
Interlock connections

Inlet Hose Connection: Male camlock 2" inlet fittings

Outlet Hose Connection: Male camlock 2" outlet fittings
4" diameter 18 ft height stack for the Air Stripper

Power Requirements: 240 Volt, 3 phase, 200 Amp service
(Main fused disconnect located outside trailer)

Texas • Colorado • Michigan • New Jersey • Connecticut