



Thermal/Catalytical Oxidizer Propane or Natural Gas Unit# 50

Environmental Treatment Specialists



General Specifications: 750 SCFM @4" Hg

Trailer: 8 ft wide x 16 ft long x 9 ft height
3,500 pound double axle trailer

Main Equipment: 5 Hp XP Blower
Flame Arrestor
Heat Exchanger
Burner (500,000 BTU/Hr)
Stainless Steel Reactor
Catalyst (option)
Circular Chart Recorder (inlet and outlet temperatures)
Completely enclosed system
Vacuum and pressure gauges, sample ports

Trailer Specifications: System is mounted on back of flat bed trailer

Control Panel: PLC (Program Logic Controller)
On/Off switch all components
Emergency stop button
Fault lights and reset
Interlock connections

Inlet Hose Connection: 1 - Male camlock 6" inlet fittings (30 ft hose w/system)
Auto dilution valve

Outlet Hose Connection: 8" air stack from top of enclosure (20ft. high)

Power Requirements: 230 volt, 3 phase, 60 Amp service (20 ft electrical cord)
Propane or Natural Gas connection

ProAct Services Corporation

Corp Office: 231-843-2711
Gulf Coast: 210-862-6467
or 713-202-6351
Midwest Office: 231-342-1115
East Coast Office: 203-262-1200

www.proact-usa.com

Texas • Colorado • Michigan • New Jersey • Connecticut