



## Ozone Injection System Unit# 82

### Environmental Treatment Specialists



General Specifications: Ozone Injection System  
12 pounds/day 255g/hr of Ozone  
Delivery pressure 50 psi

Trailer: 8ft wide x 20 ft long x 7 ft height  
45,000 pound double axle trailer

Main Equipment: 2-6 pound/day. PB-6 Ozonology System  
15 HP Rotary Screw Air Compressor  
Air Dryer  
126 cfm Air Sep Oxygen Generator  
120 gallon Holding Tank  
Pressure and Flow Transducers  
80 gallon Air Pressure Tank  
Ozone Leak Detector  
15 Well Manifold, 3 banks of 5 wells, 3/8" threaded outlets  
Flow to each bank can be automatically alternated by PLC  
Flow Meters, control flow valves and pressure gauges each well



Trailer Specifications: Insulated Trailer  
Thermostatically heated and fan cooled  
Lights  
Aluminum diamond plated floor  
Outside light



Control Panel: HAO switch – all components  
ProControl computer control  
Cell phone communication package w/PLC  
Remote monitoring capability  
Emergency stop button  
GFI

Power Requirements: 240 Volt, 3 phase, 100 Amp services  
(Main fused disconnect located outside trailer)  
55 KW Diesel power generator

#### ProAct Services Corporation

Corp Office: 231-843-2711  
Gulf Coast: 210-862-6467  
or 713-202-6351  
Midwest Office: 231-342-1115  
East Coast Office: 203-262-1200

[www.proact-usa.com](http://www.proact-usa.com)

Texas • Colorado • Michigan • New Jersey • Connecticut